

Overview


- Support H.265/H.264 video formats
- 16-channel input
- Plug & play with 16 independent PoE network interfaces
- Support HDMI and VGA independent outputs
- 4 SATA HDDs, up to 10TB for each HDD
- ANR technology to enhance the storage reliability when the network is disconnected



Technical Specifications

| | |
|---------------------------|--|
| Video/Audio Input | |
| IP Video Input | 16-ch |
| Supported camera | advidia M-series |
| Audio Input | 1-ch, RCA |
| Network | |
| Incoming Bandwidth | 320Mbps |
| Outgoing Bandwidth | 320Mbps |
| Remote Users | 128 |
| Protocols | TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS |
| Video/Audio Output | |
| HDMI/VGA Output | VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz HDMI: 4K (3840x2160)/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz |
| Recording Resolution | 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF |
| Recording Mode | Normal, Event, Manual |
| Audio Output | 1-ch, RCA |
| Camera Control | Pan/Tilt, Zoom, Focus, Iris, Preset Position, Preset Patrol, Recorded Patrol, Auto Guard |
| Synchronous Playback | 16-ch |
| Multiscreen Mode | Normal Mode: 1/4/6/8/9/16 Corridor Mode: 3/4/5/7/9/10/12/16 Web Client: 4/6/8/9/10/13/16 |

| Decoding | |
|---------------------------|--|
| Decoding format | H.265/H.264 |
| Live view/Playback | 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF |
| Capability | 1 x 12MP@30fps, 2 x 4K@30fps, 5 x 4MP@30fps, 10 x 1080P@30fps, 16 x 720P@30fps |
| SATA | 4 SATA interfaces |
| Capacity | Up to 10TB for each disk |
| Disk Array | |
| Array Type | RAID 1, 5 |
| External Interface | |
| Network Interface | 1 RJ45 10M/100M/1000M self-adaptive Ethernet Interfaces |
| Serial Interface | 1 x RS485 |
| USB Interface | Front panel: 1 x USB2.0, Rear panel: 1 x USB3.0 |
| Alarm In | 16-ch |
| Alarm Out | 4-ch |
| PoE | |
| Interface | 16 RJ-45 10M/100M self-adaptive Ethernet Interface |
| Maximum power | Max 30W for single port Max 150W in total |
| Supported Standard | IEEE 802.3af/at |
| General | |
| Power Supply | 100 ~ 240 V AC Power Consumption: ≤20W (without HDD) -10°C~+ 55°C (+14°F~+131°F), Humidity ≤ 90% RH (non-condensing) |
| Dimensions (W×D×H) | 400mm × 363mm × 74mm (15.7" × 14.3"× 2.9") |
| Weight (without HDD) | ≤4Kg (8.82lb) |



© i-PRO Co., Ltd. All Rights Reserved. i-PRO, Viewnetcam.com, Advidia, VideoInsight, ClouDE, and Unified Digital Evidence are registered trademarks or trademarks of i-PRO Co., Ltd. or i-PRO Americas Inc. in various jurisdictions. All other trademarks are the property of their respective owners.