

Panasonic IP Intercom System

Lobby Station VL-VC3900BX



1. Basic information

- Color: Black
- Dimension: 166mm*386mm*52mm
- Embedded Box Dim: 145mm*358mm*60mm
- Material: Al + Tempered glass
- Installation: Flush mount

2. Function

- Video intercom: video communication, remote unlock, apartment entrance mode and community entrance mode
- Vandal-resistant: If someone move the device, device will send alarm information to guard unit and software management
- Elevator control: call elevator, control elevator (3rd party Option)
- Customized Screen: Prepared 5 types of the picture data, such as “Panasonic”, Developer’s name, Condominium name.
- Time synchronized: device time will synchronize from center (guard unit) automatically
- Leave message: Visitor can leave a voice message with a photo
- External device: Access Controller, access Control Reader, Elevator Controller and Dry Contact
- Web configuration: engineer can set parameters on webpage
- 12V output: 12V output can give power supply to external device
- Support 2 locks: First lock connect to outdoor unit directly

3. Parameters

- Operation system: Linux
- Color camera: 200W pixels
- Max consumption: $\leq 3.47W$
- Standby consumption: $\leq 2.28W$
- Screen: 5inch
- Operation: Touch button
- Resolution: 480*272
- Voltage: 12~24VDC $\pm 10\%$
- Working Temp: -40°C~70°C
- Main frequency: 1.2 GHz
- RAM: 64MB
- Flash: 16MB
- IP grade: IP54
- Port: RJ45
- Protocol: TCP/IP
- Audio and video codec: G.711/H.264

Spec & Function is subject to change without notice