



Main

Range	EcoStruxure Security Expert
Product brand	Schneider Electric
Product or component type	Keypad
Device application	Control
Control button type	12 numeric touch button capacitive 7 operation touch button capacitive 4 for navigation touch button capacitive
Colour tint	White

Complementary

Display type	Backlit LCD: 2 lines of 16 characters
[Ue] rated operational voltage	11...14 V DC
[Ie] rated operational current	60 mA in operation 95 mA maximum
Discrete input type	2 zone for standard input 4 zone for duplex mode input
Discrete output type	4 configurable for signaling 1 open collector (50 mA)
Local signalling	LED, status front face red LED, armed front face green LED, disarmed front face buzzer
Device composition	Keypad Set of resistors
Depth	18 mm
Width	125 mm
Height	125 mm
Net weight	318 g

Environment

Ambient air temperature for operation	0...49 °C
Ambient air temperature for storage	-10...85 °C
Relative humidity	0...93 % non-condensing

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.25 kg
Package 1 Height	15.8 cm
Package 1 width	15.5 cm
Package 1 Length	3.8 cm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins